

Accellence Technology Corp.

Quick access to CS & SS Ball Valves

One-piece Ball Valves:

Item No.	Economy	Hexagon	Body Material		Bore	Working Pressure (psi)	End Connection				Handle Locking Device (Option)	Size Range
			Carbon steel	Stainless steel			T	SW	BW	FL		
B-111					R	1000						¼" ~ 2" (DN 8 ~ DN 50)
B-112					R	1000						¼" ~ 2" (DN 8 ~ DN 50)
B-113					R	1000						¼" ~ 2" (DN 8 ~ DN 50)
B-114			bar		R	2000						¼" ~ 2" (DN 8 ~ DN 50)
B-115					R	2000						¼" ~ 1" (DN 8 ~ DN 25)
					R	1500						1¼" ~ 2" (DN 32 ~ DN 50)

R : Reduce bore F : Full bore T : Thread SW : Socket weld BW : Butt weld FL : Flange



B-111



B-113



B-115



B-112



B-114

Accellence Technology Corp.

Quick access to CS & SS Ball Valves

Two-piece Ball Valves (Threaded End):

Item No.	Economy	Actuator Mounting Pad		Body Material available		Bore	Working Pressure (psi)	End Connection				Handle Locking Device (Option)	Size Range
		Two threaded hole	ISO 5211 Direct Mount	Carbon Steel	Stainless Steel			T	SW	BW	FL		
B-211						F	1000						¼" ~ 4" (DN 8 ~ DN 100)
B-212						F	1000						¼" ~ 2" (DN 8 ~ DN 50)
B-213						F	1000						¼" ~ 2" (DN 8 ~ DN 50)
B-216						F	1000						¼" ~ 2" (DN 8 ~ DN 50)
							800						2½" ~ 3" (DN 65 ~ DN 80)

R : Reduce bord F : Full bore T : Thread SW : Socket weld BW : Butt weld FL : Flange



B-211



B-212



B-213



B-216

CAT01-01-051030

Accellence Technology Corp.

Quick access to CS & SS Ball Valves

Two-Piece Ball Valves (Flange End) :

Item No.	Economy	Actuator Mounting Pad		Body Material		Bore	Nominal Pressure	End Connection				Handle Locking Device (Option)	Size Range
		ISO 5211	ISO 5211 Direct Mount	Carbon steel	Stainless steel			T	SW	BW	FL		
B-611						F	Class 150						1/4" ~ 4" (DN 8 ~ DN 100)
B-612						F	PN 40						1/2" ~ 2" (DN 15 ~ DN 50)
							PN16						2 1/2" ~ 4" (DN65~ DN 100)
B-613						F	JIS 10K						1/2" ~ 8" (DN 15 ~ DN 200)

R : Reduce bord F : Full bore T : Thread SW : Socket weld BW : Butt weld FL : Flange



B-611



B-612



B-613

Accellence Technology Corp.

Quick access to CS & SS Ball Valves

Three-piece Ball Valves:

Item No.	Actuator Mounting Pad		Body Material		Bore	Working Pressure (psi)	Nominal Pressure	End Connection				Handle Locking Device (Option)	Size Range
	ISO 5211	ISO 5211 Direct Mount	Carbon steel	Stainless steel				T	SW	BW	FL		
B-311					F	1000							1/4" ~ 4" (DN 8 ~ DN 100)
B-312					F	1000							1/4" ~ 4" (DN 8 ~ DN 100)
B-313					R	2000							1/4" ~ 1" (DN 8 ~ DN 25)
						1500							1 1/4" ~ 2" (DN 32 ~ DN 50)
B-314					F	2000							1/4" ~ 2" (DN 8 ~ DN 50)
B-315					F		Class 150						1/2" ~ 4" (DN 15 ~ DN 100)
							PN 40						
							JIS 10K						
B-317					F	1000	PN 63						1/2" ~ 4" (DN 15 ~ DN 100)

R : Reduce bord F : Full bore T : Thread SW : Socket weld BW : Butt weld FL : Flange



B-311



B-312



B-313



B-314



B-316



B-315